



#2 Dairy Manure Storage & Greenhouse Gas Mitigation Opportunities

Jenifer Wightman, Peter Woodbury, Curt Gooch, & Peter Wright
 Cornell University, Soil & Crop Sciences and Biological & Environmental Engineering

#2 Overview	1
Fast Facts	2
Introduction.....	2
Environmental Concerns.....	2
Summary Of Regulations Of GHG Emissions	3
Goal	3
Summary Of Potential GHG Reduction Practices From Manure	3
#2 In Depth	3
GHG Emissions From Manure.....	4
Managing GHG From Vs And N By Manure Management System.....	6
Summary Of Conceptual Strategies For Managing Manure GHG	7
MITIGATION OPPORTUNITY 1: Optimizing Animal Feed.....	7
MITIGATION OPPORTUNITY 2: Separate Manure (Solid Storage + Liquid Storage With Cover & Flare)	8
MITIGATION OPPORTUNITY 3: Liquid/Slurry Anaerobic Digestion For Energy Generation	10
Vocabulary.....	12
Resources And Tools.....	13
References.....	14
Credits & Acknowledgments	15

#2 Overview

#2 Dairy Manure Storage & Greenhouse Gas Mitigation Opportunities

Jenifer Wightman, Peter Woodbury, Curt Gooch, & Peter Wright

Cornell University, Soil & Crop Sciences and Biological & Environmental Engineering

FAST FACTS

- **Trends:** Due to increasing farm size and water quality requirements, more farms are storing manure in order to apply valuable nutrients to cropland during the growing season.
- **An imperative to act:** Stored manure is often anaerobic (low oxygen) and produces methane, a greenhouse gas (GHG) that is 34 times more potent than carbon dioxide (CO₂) over 100 years (86 times more potent over 20 years). If methane is combusted it greatly reduces farm GHG emissions.
- **A concern for implementation:** Stored manure also produces N₂O (a potent GHG 298 times more potent than CO₂) and other gases such as hydrogen sulfide (H₂S) that can impact health.
- **An opportunity for proactive change:** Many carbon-trading programs recognize methane destruction; methane can also be used to generate useable energy on and off farms.

INTRODUCTION

Society increasingly expects agriculture to produce food in a manner that maintains environmental quality. In the past, daily spreading of manure, with the potential to contaminate surface waters, was common particularly during fall or winter when crops are not growing and frozen ground increases surface runoff of nutrients to streams (Williams et al., 2011, Wightman & Woodbury 2016). To address water quality, manure is stored in a solid stack (less often) or in a liquid storage facility (more often) for many months so manure can be spread on dates closer to when crops can take up the nutrients, reducing the potential for pollution of surface and groundwater. However, these improvements for water quality may have drawbacks when considering greenhouse gas (GHG) emissions (Gooch, 2005a).

ENVIRONMENTAL CONCERNS

Methane (CH₄) and nitrous oxide (N₂O) are potent GHG and should be considered when evaluating manure management. For more general information about GHG in agriculture, see [Information Sheet #1](#). Dairy manure is about 90% moisture and 10% solids (ASABE, 2006), with a portion of those solids being carbon compounds called volatile solids (VS), and also various nitrogen (N) compounds. Some of the VS are precursors for CH₄ and some of the nitrogen compounds are precursors for N₂O. More anaerobic (low oxygen) manure management conditions, as found in liquid storage, cause more CH₄ production. More aerobic (high oxygen) manure management conditions, such as daily spreading or composted solids, prevent CH₄ production. The opposite pattern is true for N₂O: when manure-N is stored more anaerobically, N will not convert to N₂O (and has great benefit for reducing synthetic N fertilizer needs during spring planting); when manure-N is stored under aerobic conditions (e.g. composted solids), more N₂O is released. These two gases are important because CH₄ is 34 times more potent as a GHG than CO₂ while N₂O is 298 times more potent over 100 years. This is potency is referred to as the Global Warming Potential or GWP; see [Information Sheet #1](#). To note, there is significantly more VS than N in the manure, so while N₂O is a more potent GHG than CH₄, there is significantly greater potential to produce

more CH₄. Besides GHG, other emissions including ammonia, hydrogen sulfide, and other odor causing compounds are often released from manure storage. In high concentrations these toxic gases can cause damage and even death to humans and other animals.

SUMMARY OF REGULATIONS OF GHG EMISSIONS

Policies and regulations, such as Concentrated Animal Feeding Operation (CAFO) permitting, Total Maximum Daily Load (TMDL) requirements for certain watersheds, and other watershed protection efforts throughout NYS, have led to more storage capacity on farms to facilitate better management of manure for water quality. There are no regulations of GHG emissions from agriculture in NYS.

GOAL

This Information Sheet is intended to help dairy farmers and their advisors navigate meaningful methods for reducing GHG emissions from manure management systems. Three major opportunities are summarized below.

SUMMARY OF POTENTIAL GHG REDUCTION PRACTICES FROM MANURE

Description of Strategy	Opportunities	Considerations
Optimized animal feed	<ul style="list-style-type: none"> Reduce nitrogen in animal feed to reduce N₂O emissions from manure storage. Improve diet efficiency to reduce total inputs, reduce VS in the manure, and potentially reduce the enteric emissions of CH₄ from the cow. <p>Other benefits: Feed efficiency saves money.</p>	<ul style="list-style-type: none"> Requires animal diet planning and testing of diet and manure.
Manure storage with cover and flare for methane destruction	<ul style="list-style-type: none"> Methane capture with a cover + combustion with a flare reduces the GWP of CH₄ from 34 to 1. Documented and verified CH₄ destruction can qualify for carbon credits. State and federal agencies offer competitive funding for manure cover and flare systems. <p>Other benefits: Manure covers exclude rain reducing storage size. Excluding rainfall can reduce hauling costs. A cover prevents rainfall from causing overflow of storages. Covers can control storage odor and improve neighbor relations.</p>	<ul style="list-style-type: none"> Covers + flares cost money, require labor & maintenance. Covers last ~10-20 years and will need to be replaced. Carbon markets are not mature. CH₄ is a highly flammable gas requiring new safety considerations. Storing manure can produce hydrogen sulfide (H₂S), a deadly gas. Manure solid/liquid separation is required.
Anaerobic Digestion System (ADS) methane destruction + energy generation	<ul style="list-style-type: none"> Methane capture and combustion for generating electricity reduces the GWP of methane from 34 to 1. AD can be used to generate heat and power on farm, reducing fossil fuel emissions. Grants are available for ADS-electricity AD may qualify for carbon credits and/or renewable energy credits if documented and verified. <p>Other benefits: ADS can control odors from storage and spreading, reduce electric costs, and improve neighbor relations.</p>	<ul style="list-style-type: none"> ADS intentionally produce additional methane, which if not properly combusted in an engine, boiler, or flare can cause increased farm GHG emissions. AD systems are expensive to construct and require regular maintenance. CH₄ is a highly flammable gas requiring new safety considerations. Storing manure can produce hydrogen sulfide (H₂S), a deadly gas. H₂S can also corrode equipment; corrosion is reduced by proper design. Capital costs may not be recouped from sale of electricity.

#2 In Depth

#2 Dairy Manure Storage & Greenhouse Gas Mitigation Opportunities

Janifer Wightman, Peter Woodbury, Curt Gooch, & Peter Wright

Cornell University, Soil & Crop Sciences and Biological & Environmental Engineering

Target Audience: Educators and technicians helping dairy farmers manage stored manure

Target Greenhouse Gases (GHG): Methane (CH₄) and nitrous oxide (N₂O)

Questions by Educator to help in Farmer Planning

What type and number of animals do you manage (e.g. 20% heifers, 80% milking)?

Does your farm store manure?

If no,

How do you currently manage your manure?

Are you experiencing any issues with your manure management practices?

What are your near and long term manure management goals?

Are you interested in exploring GHG mitigation options?

If yes,

How many months of storage capacity?

What kind of storage (e.g. solid under a roof, liquid in earthen containment)?

Are you experiencing any issues with your manure management practices?

What are your near and long term manure management goals?

Are you interested in exploring GHG mitigation options?

GHG EMISSIONS FROM MANURE

Different manure storage systems have different amounts of available oxygen that impact the potential for greenhouse gas (GHG) production. When a storage unit has no free oxygen (anaerobic, such as stored liquid manure), CH₄ is produced (Kebreab et al., 2006). These anaerobic systems reduce N₂O emissions. In contrast, high oxygen (aerobic) systems inhibit CH₄ production but have increased N₂O emissions. Both CH₄ and N₂O are GHG.

Over 100 years, CH₄ is 34 times as potent as carbon dioxide (CO₂); over 20 years CH₄ is 86 times as potent as CO₂ (IPCC, 2013) making it an even more important target for near-term GHG mitigation efforts (Shoemaker et al., 2013). As N₂O is 298 times as potent as CO₂ (over 100 years, IPCC, 2013), both CH₄ and N₂O must be considered when evaluating the GHG emissions from a change in manure management systems.

Emissions of CH₄ and N₂O from manure storage depend on the storage conditions of the N and volatile solid (VS) content in the manure. Conditions that promote CH₄ emissions include the mass of VS, storage time, and temperature (Dong et al., 2006, Hashimoto et al., 1981). Table 1

below illustrates how a change away from daily spread to more anaerobic storage systems has more than doubled farm GHG despite a decrease in total animal number and increase in milk productivity.

Table 1. Effect of manure management strategy on total greenhouse gas (GHG) emissions in NYS.*

	Daily spread†	Solids	Liquids‡	Total	
1992					
Percentage waste management system (%)	80.6	3.6	15.8		
	Mg CO ₂ e yr ⁻¹				% GHG
N ₂ O direct	0	11,427	49,572	60,999	8.7
N ₂ O Volatilization indirect§	50,736	6,171	25,778	82,684	11.8
N ₂ O Runoff indirect¶	0	0	521	521	0.1
CH ₄ #	52,016	18,745	487,907	558,668	79.5
1992 TOTAL	102,752	36,342	563,777	702,872	
2012					
Percentage waste management system (%)	42.6	10.7	46.6		
	Mg CO ₂ e yr ⁻¹				% GHG
N ₂ O direct	0	28,641	124,251	152,892	9.9
N ₂ O Volatilization indirect§	22,709	15,466	64,610	102,786	6.6
N ₂ O Runoff indirect¶	0	0	1,305	1305	0.1
CH ₄ #	23,282	46,982	1,222,913	1,293,178	83.4
2012 TOTAL	45,992	91,090	1,413,078	1,550,160	

* From Wightman and Woodbury 2016

†In 1992 there were 721,286 milking cows, and 81% of manure was daily spread. In 2012 there were 610,712 milking cows and 48% of manure was daily spread (Wightman & Woodbury 2016).

‡Using USEPA methane conversion factor values for daily spread, solids, and liquid-slurry.

§N₂O Volatilization indirect refers to N that volatilized from the point source and redeposited at a remote location and subsequently converted to N₂O (not including emission on land application).

¶N₂O Runoff indirect refers to N that has run off from the point source to a remote location and subsequently converted to N₂O (not including emission on land application).

The data in Table 1 indicate several important considerations about GHG emissions for manure management. First, roughly 80% of manure management emissions come from CH₄ and 20% from N₂O. Second, there are three different mechanisms by which manure N can become N₂O (directly emitted and indirectly emitted through leaching and volatilization and re-deposition). Third, there has been a change in practice away from daily spread (81% of manure was daily spread in 1992 compared to 43% of manure daily spread in 2012).

Table 2 indicates how changes in practice have impacted GHG per unit milk.

Table 2. Effects of changes in manure management on methane emissions in NYS (1992–2012).*

	No. animal units	Methane produced†	
		Milk produced Mg	Mg CO ₂ e yr ⁻¹ Mg CO ₂ e Mg milk ⁻¹
1992 herd total	1,414,436	5,246,878	558,668
2012 herd total	1,197,601	5,988,260	1,293,178
2012 herd with 1992 WMS‡	1,197,601	5,988,260	473,023

* From Wightman and Woodbury 2016

†Using only USEPA methane conversion factors for daily spread, liquid-slurry, and solid manure.

‡Manure from the 2012 cow population is managed by the 1992 waste management system (WMS), which was predominantly daily spread.

The data in Table 2 indicate that even though the 1992 NY dairy herd was larger (milking cows plus replacement heifers), the 1992 manure management produced half the CH₄ per unit milk of the smaller 2012 herd (Wightman & Woodbury, 2016). However, if the 2012 herd used the 1992 manure management practices, it would have produced less total GHG emission as well as less GHG per unit milk. This result indicates that milk production efficiency practices have reduced the amount of manure per unit milk, thus reducing the GHG precursors that could have been converted to CH₄ and N₂O.

MANAGING GHG FROM VS AND N BY MANURE MANAGEMENT SYSTEM

Different manure storage systems allocate the VS and N differently between the liquid and solid portions of the manure as shown for separation examples in Table 3.

Table 3. Solid-Liquid separation impact on volume, VS, & N.

Separator Type	Screen size mm	Fraction liquid % original mass	Vs in liquid %	N in liquid % total N	Author
Screw press	0.80	82%	44%	79%	Rico et al., 2011
Belt press	0.30	88%	48%	n/a	Sutaryo et al., 2013
Screw press	0.50	n/a	44%	78%	Chastain 2009
Screw press	0.75	77%	32%	77%	Gooch et al., 2005b
Roller separator	n/a	78%	54%	76%	Gooch et al., 2005b
AVERAGE		81%	45%	77%	

These data show three things. First, they illustrate that manure is mostly liquid (separated with screw press, belt press, or roller separator). Second, the N partitions relatively equally between the liquid and solid portions of the manure. Third, the VS also partitions relatively equally between the liquid and solid portions, but favoring the solid portions on a mass basis. This partitioning is important when selecting a manure management system. The various effects that manure management practices have on CH₄ and N₂O production are summarized in Table 4.

Table 4. How manure management practices impact production of N₂O and CH₄

Practice	Oxygen condition	Manure component	Portion of GHG precursor	N to N₂O	VS to CH₄
Daily spread	Aerobic	Liquid+Solids	100% N and 100% VS	HIGH	~none
Separated Solids ‡	Mostly Aerobic	Solids Only	~25% N and ~50% VS	HIGH	LOW
Separated Liquids ‡	Anaerobic	Liquids Only	~75% N and ~50% VS	LOW	HIGH
Liq/Slurry	Anaerobic	Liquids+Solids	100% N and 100% VS	LOW	HIGH*
Liq/Slurry (ADS)	Anaerobic	Liquids+Solids	100% N and 100% VS	LOW	Very HIGH*

‡ Solids only and liquids only should be ‘combined’ when thinking about total GHG potential.

* The VS in lignin solids is generally more difficult to convert into CH₄. However, an anaerobic digester facilitates the conversion of the VS by controlling the temperature and retention time. This is beneficial in AD energy generating systems because it creates more CH₄ gas for increased energy production.

Table 4 lists common manure management practices based on oxygen levels within the management practice starting with the highest N₂O emissions (most aerobic or high oxygen systems) at the top and the highest CH₄ production at the bottom (anaerobic or low oxygen systems). It also illustrates how these manure management practices partition their GHG precursors (VS and N) and the likelihood of these GHG precursors to be converted to CH₄ or N₂O. Generally, aerobic systems produce the most N₂O, anaerobic systems produce the most CH₄.

SUMMARY OF CONCEPTUAL STRATEGIES FOR MANAGING MANURE GHG

Conditions that may reduce GHG precursors in manure storage.

- Increasing the feed efficiency (reduces amount of manure per unit milk), thus reducing VS and N precursors available in the manure to be converted to CH₄ and N₂O emissions.
- Considering the amount of other wastes (bedding, imported food waste) placed in the storage that add additional N and VS precursors available for conversion to N₂O and CH₄ on farm.

Conditions that may reduce the formation of GHG.

- Maintaining the manure-N in anaerobic conditions can help store the N (reduce N to N₂O conversion) until field application during the growing season so the plants absorb it (thus reducing purchase of synthetic N).
- Separating manure solids retains the majority of N in the liquid portion that if stored anaerobically, produce relatively little N₂O, keeping the N for spring field application. Separation also removes ~50% of the VS to the more aerobic solid storage thus reducing potential CH₄ emissions. It is estimated that separation may reduce overall GHG emissions by 20% but is difficult to quantify the total CH₄+N₂O benefit of separation on a variety of farms and practices (Jayasundara et al., 2016).
- As warm temperatures increase the biological conversion of VS to CH₄, reducing the amount of manure and/or storage time of manure during warmer seasons can reduce the CH₄ emitted.

Conditions that may destroy CH₄.

- Methane can be metabolized in the manure crust by bacteria. However, manure crust conditions also increase the N₂O emissions; a recent review indicates that the GHG mitigation potential of a crust can be variable. (Jayasundara et al, 2016).
- Methane can be captured and combusted (by a flare, boiler, or engine) to CO₂ and water vapor, thus significantly reducing the GWP of CH₄ from manure storage. This CH₄ destruction can be measured and be eligible for carbon credits. CH₄ combustion for energy can displace fossil fuel emission.

MITIGATION OPPORTUNITY 1: OPTIMIZING ANIMAL FEED

Improved diet can mitigate emissions in four ways. 1) It can reduce enteric emissions (not assessed here because it is not a manure management strategy). 2) Maximal feed utilization results in less VS in the manure per unit milk, thus reducing the CH₄ precursors per unit milk. To

note, Table 2 above illustrates that NY dairy farmers have been increasing milk production efficiency. 3) If diet is monitored so no excess N is fed, there will be less N in manure available to be potentially turned into N₂O. 4) This feed efficiency can also reduce emissions from producing the extra feed (upstream GHG emissions from fertilizing, harvesting, transporting grain etc.). By reducing the N and VS available in the manure and increasing the milk production efficiency, the farm is reducing the quantity of N and VS available to potentially be converted to N₂O and CH₄ in the manure management systems.

MITIGATION OPPORTUNITY 2: SEPARATE MANURE (SOLID STORAGE + LIQUID STORAGE WITH COVER & FLARE)

SOLID portion (N₂O and CH₄ production)

The solid portion, because it is generally more aerobic, has low CH₄ emission despite storing ~50% of the VS. In contrast, while only ¼ of the N precursors end up in the solid portion, the fluctuating aerobic/anaerobic condition of the solid manure has the capacity to cause a significant increase in N₂O emissions compared to N stored in anaerobic liquid/slurry storage. A recent review indicates aerated composting in warm summer months is preferable to a stockpile for GHG (Jayasundara et al., 2016) but may not be preferable for N-retention.

LIQUID portion (N₂O and CH₄ production)

Anaerobic liquid storage of manure N is effective in keeping N from converting to N₂O (for liquid/slurry or separated liquids) as well as retaining N for spring field application. As shown in Table 3, separation retains most of the manure-N in the liquid portion. While liquid storage keeps N₂O emissions low, the anaerobic conditions of liquid storage make manure CH₄ emissions a significant source of farm GHG during warm months. Farms could spread the liquid frequently in the summer thus minimizing anaerobic storage during warm temperatures favorable for converting VS to CH₄. If frequent summer spreading of the liquids is unrealistic, farms may consider placing a cover on their liquid manure storage to capture the methane and convert the methane to carbon dioxide by flaring it. Additionally, covers prevent extreme weather-event induced overflows, reduce rainwater collection to reduce hauling costs, enhance the N retention in the manure, and reduce odors from liquid manure storage. This has been done on farms in NYS (Wightman & Woodbury 2016). Figure 1 is an image of an existing cover in NY followed by a review of information from three farms that have storage equipped with a cover and flare.



Figure 1. Manure cover on New York dairy farm, photo courtesy of Fessenden Dairy

A pilot project performed by Environmental Credit Corp (ECC) placed covers (1.5 mm thick high-density polyethylene) and flares on three existing NY dairy farm manure storage units from 2008-2009. The storage units contained only separated liquids; farm size ranged from 1,265 – 1,710 animal units (AU) (Subler, 2011). Animal populations were tracked and used to estimate volatile solid outputs. Biogas flow was continuously measured and recorded, and methane concentration readings were taken quarterly. Overall, flaring was 80% effective in burning the combustible components in the biogas; in the winter months the flare rarely operated (Table 5).

Table 5. Monthly biogas data averaged across 3 covered manure storage units on dairy farms in New York during 12 consecutive months between 2010 and 2011.

	m³ biogas	% CH₄†	AFE ‡
Jan	5,859	34%	0.2
Feb	3,129	34%	0.0
Mar	4,432	34%	0.2
Apr	5,839	47%	0.0
May	5,738	47%	0.3
Jun	14,183	47%	0.8
Jul	30,585	65%	1.0
Aug	34,291	65%	1.0
Sep	33,265	65%	1.0
Oct	30,793	52%	0.9
Nov	11,841	52%	0.6
Dec	3,615	52%	0.1
TOTAL	183,568	57%	0.8

‡ AFE – annual flare effectiveness is a measure of the percentage of methane produced and effectively destroyed by flaring on an annual basis. Note, most methane is produced in the summer when the flare is the most effective.

† % methane in biogas (measurements taken quarterly)

The data in Table 5 illustrate several things. First, liquid-only storage on farm produces a lot of biogas (averaging 57% CH₄ concentration). Second, most CH₄ is produced in the warm summer months. Third, when the CH₄ concentration is low in the biogas, the flare is less effective, because there is less CH₄ to combust and the flares were not designed for low methane concentrations. Fourth, since most gas is produced in the summer months with high CH₄ concentrations, the flare can be 80-90% effective at destroying the annual CH₄ emissions. Note, these are actual covers and flares from trials implemented; the CH₄ destruction could be improved with increased capital investment and management.

Table 6. Estimated costs for manure storage unit covers with a 10-year* lifespan†.

Budget Category	Large Cover:1000-Milking Cows#	Medium Cover: 550-Milking Cows#
	USD	USD
Equipment	\$221,081	\$121,595
Personnel	\$25,399	\$25,399
Travel	\$3,136	\$3,136
Supplies	\$890	\$890
Contractual	\$20,947	\$20,947
Other	\$14,545	\$14,545
SubTotal	\$285,999	\$186,513
Separator	\$46,613	\$46,613
Cover Disposal	\$34,503	\$18,977
Rain water (savings/10yr) ‡	-\$62,031	-\$34,117
Interest (10 yrs at 4.5%)	\$74,337	\$53,115
Total Cost	\$379,422	\$271,100
cost per milking cow/yr	\$37.94	\$49.29
cost per Mg CO ₂ e	\$9.63	\$12.51

† Wightman & Woodbury, 2016.

‡Note, rainwater saving is estimated to be \$0.02/gallon for transport to field. We do not give a savings from N-storage as that would occur with or without the cover.

Milking cow (plus manure from 0.5 associated replacement heifers/milking cow)

*While cover manufacturers predict a 20-year life-span, we have chosen 10 years to conservatively estimate cost.

In Table 6, costs for covering a 550-cow and 1000-cow storage with a flare would range between \$270,000 and \$380,000. Note, the values are modified from data collected on five farms that installed manure covers with flares in NYS in 2008-2009. To make this system break even, the price paid per Mg CO₂e would need to be in the \$10-\$13 range. To learn more about retrofitting existing storage units for covers, or planning to build a new storage unit, please see [Information Sheet #3](#). Alternatively, one might consider installing an anaerobic digester system (ADS, see below and [Information Sheet #3](#)) to destroy CH₄ while also producing energy.

MITIGATION OPPORTUNITY 3: LIQUID/SLURRY ANAEROBIC DIGESTION FOR ENERGY GENERATION

Anaerobic digestion can be passive, as in the case for the liquid storage of manure (described above) or it can be active when a farm installs an Anaerobic Digester System (ADS) – an example of an active ADS located on a NYS dairy farm is shown in Figure 2. Currently, there are 26 operating digesters in NYS with about 1,500 candidate farms for ADS.



Figure 2. Vertical digester vessel and biogas utilization building on a 100-cow tiestall farm in NYS.

An ADS actively produces methane from a portion of the VS in manure. Well-designed systems are optimized to produce CH₄ by providing adequate retention time, uniform heating to target level, and in some cases agitation. Methane production can be increased substantially by adding VS from other sources such as food waste. From an electric generation standpoint, more methane means more energy to run the engine-generator set and/or boiler. However, if there is a leak in the system, it can also mean increased overall farm GHG emissions because more CH₄ can be produced. Increased retention time can also increase total CH₄ produced while also reducing CH₄ emissions from ADS effluent storage. To note, for every kWh produced with an ADS, a farm is displacing 0.24 kg CO_{2e} from grid-based emissions (EIA, 2014). Note, most of the GHG mitigation benefit will come from destroying the high GWP of CH₄ and not from displacing fossil-based electricity.

Table 7. Sample costs from Swiss Valley Farm, a NY dairy farm (Boerman et al, 2014)

Farm Name	Swiss Valley
Number of Milking Cows	900
Loading Rate (gal)	30,000
Percent Food Waste	0%
Retention Time (days)	30
Digester Construction	\$500,000
Digester Heating System	\$200,600
Gas Mixing System	\$44,250
Building and Plumbing	\$106,500
Electrical Generator Set	\$350,000
Solid Separation Building	\$135,000
Engineering/Administrative	\$355,000
Total Cost	\$1,691,350+

+This cost was offset by a NYSERDA grant and a federal tax credit.



Figure 3. A view of the Swiss Valley Farm Anaerobic Digester System

ADS may contribute to farm sustainability in other ways by making a farm energy-self-sufficient if electric prices fluctuate. Farms will have to calculate how well the energy savings from generating electricity on-farm fit with the larger farm management plan and significant cost of constructing and operating an ADS. To learn about installing an ADS, see [Information Sheet #3](#))

Important safety note: Methane is highly combustible under certain conditions. Additionally stored manure can produce a dense gas called hydrogen sulfide (H₂S) that is deadly. Careful management of these gases is required to maintain safety.

VOCABULARY

Aerobic: Having oxygen in the system (for example in the case of manure management, an actively mixed compost aerates the solids). See also Anaerobic.

Anaerobic: Lacking free oxygen in the system (like liquid manure storage that is not aerated). See also Aerobic.

Anaerobic Digester Systems (ADS): engineered systems that regulate temperature, pH, and retention time to promote a synergistic relationship between bacteria, including methanogens, to produce more methane from manure with the intention of producing renewable energy from the biogas.

Greenhouse Gas (GHG): Any gas that causes atmospheric warming by absorbing infrared radiation in the atmosphere (common greenhouse gases include water vapor, carbon dioxide (CO₂), methane (CH₄), nitrous oxide (N₂O)).

Global Warming Potential (GWP): The potency of a gas to contribute to global warming is referred to as a Global Warming Potential (GWP). The common unit is referred to as a carbon dioxide equivalent or CO₂e. Methane and nitrous oxide are 34 and 298 times more potent than CO₂, respectively, over a 100-year period. To convert tons of methane to CO₂e, simply multiply by 34. To convert tons Nitrous Oxide to CO₂e multiply by 298.

Methane (CH₄): A potent greenhouse gas that has a Global Warming Potential (GWP) of 34 on 100-year time scale. It is formed in a variety of ways (cow rumen, liquid manure storage, wetlands, rice fields, etc.). When combusted, methane is oxidized to CO₂, a much less potent GHG.

Methanogen: bacteria that thrive in anaerobic conditions and produce methane.

Nitrogen (N): an element essential to plant and animal growth. Nitrogen is found in many forms on the farm, including nitrate, ammonia, nitrous oxide (N₂O), and other N-species.

Nitrous oxide (N₂O): A potent greenhouse gas that has a global warming potential (GWP) of 298 on 100-year time scale (meaning that it is 298 times more potent than CO₂ as a GHG). It is produced when N is present in wet agricultural fields or more aerobic manure storage systems (and inhibited in anaerobic conditions).

Volatile Solids (VS): are a more biologically available form of carbon that methanogens can convert to methane.

RESOURCES AND TOOLS

To learn more about opportunities to reduce GHG emissions, see other information sheets in this series:
Tier II Worksheets Identifying Farm & Forest GHG Opportunities

Information Sheet Topic

IS#1	Intro to Farm & Forest GHG
IS#2	Dairy Manure Storage
IS#3	Planning for Quantitative Methane Capture and Destruction from Liquid Dairy Manure Storage
IS#4	Energy Efficiency
IS#5	Nitrogen Fertilizer Management
IS#6	Soil Carbon Management
IS#7	Forest Management

AEM Technical	Water Quality BMPs
Tools	http://www.nys-soilandwater.org/aem/techttools.html

REFERENCES

- American Society of Agricultural and Biological Engineers (ASABE). 2006. *Standard Manure Production Characteristics*.
- Boerman, M., J. Pronto, C. Gooch. 2014. Anaerobic Digestion at Swiss Valley Dairy: Case Study. Dairy Environmental Systems Program, Cornell University.
http://www.manuremanagement.cornell.edu/Pages/Topics/Anaerobic_Digestion.html
- Chastain, J.P. 2009. Field evaluation of a two-stage liquid-solid separation system at a California dairy. ASABE Annual International Meeting, Reno, NV. 21–24 June 2009. ASABE, St. Joseph, MI.
- Dong, H., J. Mangino, T. MacAllister, J.L. Hatfield, D.E. Johnson, K.R. Lassey, M.A. de Lima, A. Romanovskaya, D. Bartman, D. Gibb, and J.H. Martin, Jr. 2006. Emissions from livestock and manure management. In: S. Eggleston et al., editors, 2006 IPCC guidelines for National Greenhouse Gas Inventories. National Greenhouse Gas Inventories Programme, IGES, Japan.p. 10.11–10.87.
- Energy Information Administration (EIA). 2014. “New York Electricity Profile”
<https://www.eia.gov/electricity/state/newyork/index.cfm>.
- Gooch, C.A. 2005a. Manure Treatment, Water Quality, and Air Emissions: They are all linked. Proceedings from the Dairy Manure Management: Treatment, Handling, and Community Relations Conference, Syracuse, NY. March 15-17, 2005. NRAES-176.
- Gooch, C.A., S. Inglis, and K. Czymmek. 2005b. Mechanical solid-liquid manure separation: Performance evaluation on four New York State dairy farms: A preliminary report. ASAE Meeting Presentation, 17 July 2005, Tampa, FL.
- Hashimoto, A.G., V.H. Varel, and Y.R. Chen. 1981. Ultimate methane yield from beef-cattle manure: Effect of temperature, ration constituents, antibiotics and manure age. *Agric. Wastes* 3:241–256. doi:10.1016/0141-4607(81)90011-1
- Intergovernmental Panel on Climate Change. 2006. Emissions from livestock and manure management. In: S. Eggleston et al., editors, IPCC guidelines for national greenhouse gas

- inventories. Vol. 4. Agricultural, forestry and other land use. IGES, Kanagawa, Japan. p. 10.1–10.87.
- Jayasundara, S., J.A.D. R.N. Appuhamy, E. Kebreab, and C. Wagner-Riddle. 2016. Methane and nitrous oxide emissions from Canadian dairy farms and mitigation options: An updated review, *Canadian Journal of Animal Science*. 96:306-331.
- Kebreab, E., K. Clark, C. Wagner-Riddle, and J. France. 2006. Methane and nitrous oxide emissions from Canadian animal agriculture: A review. *Can. J. Anim. Sci.* 86:135–158. doi:10.4141/A05-010
- Rico, C., J.L. Rico, I. Tejero, N. Munoz, and B. Gomez. 2011. Anaerobic digestion of the liquid fraction of dairy manure in pilot plant for biogas production: Residual methane yield of digestate. *Waste Manag.* 31:2167–2173. doi:10.1016/j.wasman.2011.04.018
- Shoemaker, J.K., D.P. Schrag, M.J. Molina, and V. Ramanathan. 2013. What role for short-lived climate pollutants in mitigation policy. *Science* 342:1323–1324. doi:10.1126/science.1240162
- Subler, S. with Environmental Credit Corp. 2011. Providing carbon credit revenue for the adoption of lagoon covers on hog farms in North Carolina and dairies in New York. USDA–NRCS 69-3A75-7-145. http://www.nrcs.usda.gov/Internet/FSE_DOCUMENTS/stelprdb1046766.pdf (accessed 1 July 2016).
- Sutaryo, S., A.J. Ward, and H.B. Moller. 2013. Anaerobic digestion of acidified slurry fractions derived from different solid-liquid separation methods. *Bioresour. Technol.* 130:495–501. doi:10.1016/j.biortech.2012.12.037
- Wightman, J.W., P.B. Woodbury. 2016. New York Dairy Manure Management Greenhouse Gas Emissions and Mitigation Costs (1992-2022). *J. Environ. Qual.* 45:266-275. doi:10.2134/jeq2014.06.0269
- Williams, M.R., G.W. Feyereisen, D.B. Beegle, R.D. Shannon, G.J. Folmar, and R.B. Bryant. 2011. Manure application under winter conditions: Nutrient runoff and leaching losses. *Trans. ASABE* 54:891–899. doi:10.13031/2013.37114

CREDITS & ACKNOWLEDGMENTS

Authors, Jenifer Wightman, Peter B. Woodbury, Curt Gooch, and Peter Wright

Contact Info: jw93@cornell.edu, pbw1@cornell.edu, pew2@cornell.edu,
cag26@cornell.edu

Date: Last updated 2017

Funders: This work was supported by the USDA National Institute of Food & Agriculture, Hatch Projects 223995 and 1004302, and by the NYS Soil & Water Conservation Committee’s Climate Resilient Farming program.

Collaborators: Cornell Institute for Climate Change & Agriculture (D. Grantham) and NYS Department of Agriculture & Markets (G. Spitzer, G. Albrecht, B. Steinmuller).

